

Presented at the FIG Working Week 2016,  
May 2-6, 2016 in Christchurch, New Zealand

# Terrestrial laser scanner for the deformations monitoring and buildings damage

**Giuseppina Vacca**

**A. Dessi, F. Mistretta, F. Stochino**

**DICAAR, Dep. of Civil and Environmental Engineering and  
Architecture  
University of Cagliari (Italy)**



# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

Organised by



Platinum Partners



Diamond Partner





## Introduction

The work presents the use of the terrestrial laser scanner to study and to assess damaged buildings.

As known, terrestrial laser scanner provides a contactless 3D model of an object or building. The knowledge of a 3D model of a building give the opportunity to study the deformations and quantify the damages with high accuracy.





# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

## Introduction

The monitoring and measuring of the compromised building play an important role in the engineering field, because allow to make decisions about the possibility to restore or eventually destroy it.






# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

## Case study: Burned industrial building

from disaster





# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster



Platinum Partners:



Diamond Partner






# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster





## Equipment



### Faro 3D Laser Focus

Range 0.6 m – 120 m  
 Linear distance error of  $\pm 2\text{mm}$  (10m and 25m)  
 vertical visual field of  $305^\circ$  and a horizontal one  
 of  $360^\circ$   
 vertical and horizontal resolution is  $0.009^\circ$   
 scanning speed of 976.000 points/sec



### JRC Reconstructor Software v. 3.1.0



# FIG Working Week 2016


CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

**22 scanning** with  
resolution **6 mm/10 m**

- 18 indoor
- 3 indoor at the first floor (to verify the ceiling)
- 3 outdoor







# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster



Platinum Partners:



Diamond Partner






# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016


Recovery

from disaster

## Columns



Structural elements scheme



Scheme of the column cross-section center of gravity detection




# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

## Columns

from disaster



Platinum Partners:



Diamond Partner





# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

Column 8

Column 7

Column 6

Column 5

Column 4


Column 9




Section 1 - 1.0 m



Section 2 - 3.2m



Section 3 - 3.6m



Section 4 - 5.2m




# FIG Working Week 2016


CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery


from disaster




(a)




(b)



(c)



(d)



Platinum Partners:



Diamond Partner








# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster






# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

## Beams






# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

## Recovery

from disaster

Beam	L (m)	v (mm)	y (m)	$\delta$ (mm)	$r_v$ (mm)	$\alpha$ (deg)
L1	12.28	80.70	6.52	14.80	72.84	0.07
L2	12.29	22.10	12.14	24.70	-2.30	0.12
L3	12.25	36.20	12.15	38.20	1.60	0.18
L4	12.23	91.20	8.17	25.40	74.23	0.12
L5	12.26	39.90	7.65	23.60	25.17	0.11
L7	12.21	-23.40	6.97	1.60	-24.31	0.01
L8	12.26	-12.30	9.10	-7.00	-7.10	-0.03
L9	12.25	-14.90	10.32	-10.50	-6.05	-0.05
L10	12.22	-30.90	10.20	-22.00	-12.54	-0.10
L11	12.30	-19.20	3.67	-15.10	-14.69	-0.07
L12	12.24	-23.50	5.80	-7.20	-20.09	-0.03
L13	11.85	-25.20	6.65	-2.60	-23.74	-0.01
L14	11.92	-19.10	6.34	-1.00	-18.57	0.00
L15	11.89	-12.20	5.47	1.60	-12.94	0.01
L16	12.25	-31.00	8.57	-10.60	-23.58	-0.05
L17	5.57	-11.90	0.97	4.80	-12.74	0.05
L18	5.67	-9.10	4.17	-27.00	10.76	-0.27
La	12.23	-36.70	7.97	-13.80	-27.71	-0.06
Lb	12.25	-32.10	9.30	-15.90	-20.03	-0.07
T1	9.20	63.10	8.79	60.10	5.68	0.37
T2	9.33	-28.60	6.22	-0.20	-28.47	0.00
T3	9.35	32.60	8.83	32.60	1.81	0.20
T4	9.35	-11.90	3.65	-17.70	-4.99	-0.11
T5	9.35	31.00	3.75	32.10	18.13	0.20
T6	9.35	-26.00	4.83	-30.30	-10.35	-0.19
T7	9.33	12.00	1.41	15.70	9.63	0.10
T9	6.84	29.80	6.76	30.00	0.15	0.25








# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

## Ceiling





# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

## Restoration



Platinum Partners:



Diamond Partner






# FIG Working Week 2016

CHRISTCHURCH, NEW ZEALAND 2-6 MAY 2016

Recovery

from disaster

## After the restoration





## Conclusion

The TSL for the structures monitoring is a valid technique because it's not destructive and it provides the geometry of a building or structure even if this is inaccessible.

The possibility of having accurate 3D models allows the study of deformations in an accuracy way. This gives the opportunity to evaluate the interventions needed in order to restore a structure to its original state respected the costs and the work times involved.

Drawback: the complex data processing; the difficulty in extracting plans and sections from the 3D model in an automatic way and without the intervention of an operator.

